



APPLICATIONS

Eni Antifreeze Eco Plus is an amine, phosphate and nitrite free and concentrated engine coolant based on propylene glycol.

CUSTOMER ADVANTAGES

- **Eni Antifreeze Eco Plus** is a propylene glycol based product that provides a high level of environmental protection even in case of leakages and, above all, its low toxicity limits the threat to living beings.
- It is a "long life" liquid whose composition and characteristics are particularly stable. It can therefore be left in the circuit throughout the year.
- It has long-term protection against corrosion for all materials used in the engine and radiator construction, such as cast iron, aluminium, copper and solder alloys as well as a good compatibility with hoses, seals or plastics.

SPECIFICATIONS & APPROVALS

- ASTM D 3306
- CUNA NC 956-18 (ed. '04)

CHARACTERISTICS

Properties	Method	Unit	Typical
Appearance	-	-	clear
Colour	-	-	turquoise
Density at 20°C	ASTM D 1122	kg/m ³	1056
Boiling point	ASTM D 1120	°C	160
pH 10%v solution	ASTM D 1287	-	8.2





WARNINGS

- Mixture with other coolants is not advised.
- Please observe carefully manufacturer's specification on product.

HANDLING INFORMATION

- The product has to be diluted with water before use. Best working conditions are obtained by diluting with good quality water in a 33 - 60% range by volume.
- Distilled or demineralised waters suggested.
- Freezing and boiling point of the coolant depend on the concentration of the product in water:

Volume %	Freezing Point (° C)	Boiling Point (° C)
33	-17 max	103 min
50	-33 max	104 min

