



eni Rolling TNX

Safety Data Sheet

According to Regulation (EU) No. 830/2015

Revision date: 08/04/2016

Version: 3.0

Supersedes: 03/06/2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : eni Rolling TNX
Product code : 5271
Formula : 0052-2013
Product group : Trade product

This product is identified as a MIXTURE. CAS / EC / Index numbers are not applicable.
REACH registration is not applicable.

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use, Industrial use

Use of the substance/mixture : Metalworking fluid
Metalworking lubricant
Functional fluids

Do not use the product for any purposes that have not been advised by the manufacturer.

Function or use category : Lubricants and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

ENI S.p.A.
P.le E. Mattei 1 - 00144 ROMA Italy
Tel (+39) 06 59821
www.eni.com

Contact:
Refining & Marketing and Chemicals
Via Laurentina 449 00142 ROMA Italy
Tel (+39) 06 59881 Fax (+39) 06 59885700

Competent person responsible for the Safety Data Sheet (Reg. EC nr. 1907/2006): SDSInfo@eni.com

1.4. Emergency telephone number

Emergency number : CNIT +39 0382 24444 (24h) (IT + EN)

Poison centre (UK):
National Poisons Information Service Edinburgh (24h)
(+44) 844 892 0111
0870 600 6266 (UK only)
(Source: UN-WHO)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]**

Asp. Tox. 1 H304

Aquatic Chronic 3 H412

Full text of classification categories and H statements : see section 16

Adverse physicochemical, human health and environmental effects

Aspiration into lungs can cause a chemical pneumonia. Harmful to aquatic life with long lasting effects. Prolonged and repeated skin contact may cause reddening, irritation and dermatitis.

2.2. Label elements**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms (CLP) :



GHS08

CLP Signal word :

: Danger

Hazardous ingredients and/or with relevant occupational exposure limits :

: Contains: Distillates (petroleum), solvent-refined light paraffinic, Distillates (petroleum) hydrotreated light paraffinic

Hazard statements (CLP) :

: H304 - May be fatal if swallowed and enters airways
H412 - Harmful to aquatic life with long lasting effects

Precautionary statements (CLP) :

: P301+P310 - IF SWALLOWED: immediately call a POISON CENTER or doctor/physician
P331 - Do NOT induce vomiting
P273 - Avoid release to the environment
P501 - Dispose of contents/container to according to national or local regulations

Child-resistant fastening :

: No

Tactile warning :

: No

Other:

General advice :

: (Not applicable - Classified as dangerous according to (EC) No 1272/2008)

2.3. Other hazards (not relevant for classification)

Physical/chemical :

: This product is combustible, but not classified as Flammable. The creation of flammable vapour mixtures takes place at temperatures which are higher than normal ambient levels.

Health :

: If the product is handled or used at high temperature, contact with hot product or vapours may cause burns.,Any material in case of accidents involving pressurized circuits and the like, may be accidentally injected under the skin, even without external damage. In such a case, the victim should be brought to an hospital as soon as possible, to get specialized medical treatment.,Do not wait for symptoms to develop.

Environment :

: None.

Contaminants :

(air contaminants or other substances)

: In exceptional cases (i.e prolonged storage in tanks contaminated with water, and presence of anaerobic sulfate-reducing microbial colonies), the product may undergo a degradation and generate small amounts of sulfur compounds, including H2S.,See Heading 16

This substance/mixture does not meet the PBT criteria of REACH, annex XIII.

This substance/mixture does not meet the vPvB criteria of REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Composition/information on ingredients : Mineral base oil, severely refined Additives

All the mineral base oils contained in this product have a value < 3 % wt of DMSO extract, according to IP 346/92 (Nota L - Annex VI Reg (CE) 1272/2008, # 1.1.3)

Hazardous ingredients and/or with relevant occupational exposure limits : See table

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]
Distillates (petroleum), solvent-refined light paraffinic (Component)	(CAS No) 64741-89-5 (EC no) 265-091-3 (EC index no) 649-455-00-2 (REACH-no) 01-2119487067-30	80 - 90	Asp. Tox. 1, H304
Distillates (petroleum) hydrotreated light paraffinic (Component)	(CAS No) 64742-55-8 (EC no) 265-158-7 (EC index no) 649-468-00-3 (REACH-no) 01-2119487077-29	15 - 19,99	Asp. Tox. 1, H304
Alcohols, C12-14 (Additive)	(CAS No) 80206-82-2 (EC no) 279-420-3 (REACH-no) N/D	3 - 4,99	Aquatic Acute 1, H400
Reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-trans-butyl-4-hydroxyphenyl)propionate (Additive)	(CAS No) 125643-61-0 (EC no) 406-040-9 (EC index no) 607-530-00-7 (REACH-no) 01-2119878226-29	0,5 - 0,99	Aquatic Chronic 4, H413
Phenol, isopropylated, phosphate (3:1) [Triphenyl phosphate >5%] (Additive)	(CAS No) 68937-41-7 (EC no) 273-066-3 (EC index no) N/A (REACH-no) 01-2119535109-41	0,5 - 0,99	Repr. 2, H361fd STOT RE 2, H373 Aquatic Chronic 1, H410

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : In case of spontaneous vomiting, transport the victim to a hospital, to verify the possibility that the product has been aspirated into the lungs.
- First-aid measures after inhalation : In case of disturbances owing to inhalation of vapours or mists, remove the victim from exposure; keep at rest; if necessary, seek medical attention. See also Point 4.3.
- First-aid measures after skin contact : Take off contaminated clothing and shoes. Wash thoroughly with soap and water. If inflammation or irritation persists, seek medical advice. In case of contact with hot product, cool affected part with plenty of cold water, and cover with gauze or clean cloth. Call a doctor or bring to an hospital. Do not use salves or ointments, unless directed by doctor. Do not put ice on the burn.

- First-aid measures after eye contact : Rinse eyes thoroughly for at least 15 minutes. Keep eyelids well apart. If irritation persists, seek medical advice. In case of contact with hot product, cool affected part with plenty of cold water, and cover with gauze or clean cloth. Call a doctor or bring to an hospital. Do not use salves or ointments, unless directed by doctor.
- First-aid measures after ingestion : Do not induce vomiting to avoid aspiration into the lungs. If the person is conscious, rinse mouth with water without swallowing. Keep at rest. Call for medical assistance or bring to an hospital. If the casualty is unconscious, place in the recovery position. In case of spontaneous vomiting, keep head low, to avoid the risk of aspiration into the lungs. Do not give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms / injuries (general indications) : For all low-viscosity petroleum products (less than 20,5 mm²/s at 40 °C), there is the risk of aspiration into the lungs. This may occur directly after ingestion, or subsequently in case of vomiting (spontaneous or induced). In this case there is the possibility of an inflammation of the lung tissues (chemical pneumonia). This is a serious condition requiring medical treatment. Contact with eyes may cause temporary reddening and irritation. Prolonged and repeated skin contact may cause reddening, irritation and dermatitis.
- Symptoms/injuries after inhalation : This product has a low vapour pressure, and in normal conditions at ambient temperature the concentration in the air is negligible. A significant concentration may build up only if the product is used at high temperature, or in case of sprays and mists. In these cases overexposure to vapours may cause irritation to airways, nausea and dizziness.
- Symptoms/injuries after skin contact : Prolonged and repeated skin contact may cause reddening, irritation and dermatitis, due to a defatting effect. Contact with hot product may cause thermal burns.
- Symptoms/injuries after eye contact : Contact with eyes may cause a light transient irritation. Contact with hot product or vapours may cause burns.
- Symptoms/injuries after ingestion : Accidental ingestion of small quantities of the product may cause irritation, nausea and gastric disturbances. Taking into account the taste of the product, however, ingestion of dangerous quantities is very unlikely.
- Symptoms/injuries upon intravenous administration : No information available.
- Chronic symptoms : None to be reported, according to the present classification criteria.

4.3. Indication of any immediate medical attention and special treatment needed

If necessary, drain stomach by gastric lavage ONLY under qualified medical supervision. Seek medical attention in all cases of serious burns. If there is any suspicion of inhalation of H₂S (hydrogen sulphide). Administer oxygen if necessary. Immediately begin artificial respiration if breathing has ceased. The casualty should be sent immediately to hospital.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Small-size fires: carbon dioxide, dry chemicals, foam, sand or earth. Large fires: foam or water fog (mist). These means should be used by trained personnel only. Other extinguishing gases (according to regulations).
- Unsuitable extinguishing media : Do not use water jets. They could cause splattering, and spread the fire. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : This product is combustible, but not classed as flammable. The creation of flammable vapour mixtures takes place at temperatures which are higher than normal ambient levels."
- Explosion hazard : In case of losses from pressurized circuits, the sprays may form mists. Take into account that in this case the lower explosion limit for mists is about 45 g/m³ of air.
- Combustion products : Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, NO_x, H₂S and SO_x (harmful/toxic gases), Oxygenated compounds (aldehydes, etc.)

5.3. Advice for firefighters

- Firefighting instructions : Shut off source of product, if possible. If possible, move containers and drums away from danger area. Spilled product which is not burning should be covered with sand or foam. Use water sprays to cool containers and surfaces exposed to the flames. If the fire cannot be controlled, evacuate area.

Special protective equipment for firefighters	: Personal protection equipment for firefighters (see also sect. 8). Self-contained breathing apparatus.
Other information	: In case of fire, do not discharge residual product, waste materials and runoff water: collect separately and use a proper treatment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop or contain leak at the source, if safe to do so. Eliminate all ignition sources if safe to do so (e.g. electricity, sparks, fires, flares). Avoid accidental sprays on hot surfaces or electrical contacts. Avoid direct contact with released material. Keep upwind.

6.1.1. For non-emergency personnel

Protective equipment : See Section 8.

Emergency procedures : Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency.

6.1.2. For emergency responders

Protective equipment : Small spillages: normal antistatic working clothes are usually adequate. Large spillages: full body suit of chemically resistant and antistatic material. If necessary heat resistant and insulated. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Gloves made of PVA are not water-resistant, and are not suitable for emergency use. If contact with hot product is possible or anticipated, gloves should be heat-resistant and thermally insulated. Work helmet. Antistatic non-skid safety shoes or boots. Goggles and /or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory protection: A half or full-face respirator with filter(s) for organic vapours (AX) (and when applicable for H2S (B)), or a Self-contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. A Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.

Emergency procedures : Notify local authorities according to relevant regulations.

6.2. Environmental precautions

Do not let the product accumulate in confined or underground spaces. Do not let the product flow into sewers or water courses, or in any way contaminate the environment. In case of contamination of environment compartments (soil, subsoil, surface or underground waters), remove contaminated soil when possible, and in any case treat all involved compartments in accordance with local regulations. The site should have a spill plan to ensure that adequate safeguards are in place to minimize the impact of episodic releases.

6.3. Methods and material for containment and cleaning up

For containment : Soil. Contain spilled liquid with sand, earth or other suitable absorbents (non-flammable). Recover free liquid and waste materials in suitable waterproof and oil-resistant containers. Clean contaminated area. Dispose of according to local regulations. Water: Confine the spillage. Remove from surface by skimming or suitable floating absorbents. Collect recovered product and other waste materials in suitable waterproof, oil resistant containers. Recover or dispose of according to local regulations. Do not use solvents or dispersants, unless specifically advised by an expert, and, if required, approved by local authorities.

Other information : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air/water temperature, wave/current direction and speed) may significantly influence the choice of appropriate actions. Local regulations may also prescribe or limit actions to be taken. For this reason, local experts should be consulted when necessary.

6.4. Reference to other sections

Refer to chapter 16.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

- Precautions for safe handling : Ensure that all relevant regulations regarding handling and storage facilities of flammable products are followed. Do not use compressed air for filling, discharging, or handling operations. Keep away from heat/sparks/open flames/hot surfaces. Use and store only outdoors or in a well-ventilated area. During transfer and mixing operations, ensure that all equipment is correctly grounded. Avoid the build-up of electric charges. Emptied containers can contain combustible product residues. Do not cut, weld, drill, burn or incinerate empty containers or drums, unless they have been drained and cleaned. Before entering storage tanks and commencing any operation in a confined area (e.g. tunnels), carry out an adequate clean-up, and check the atmosphere for oxygen content, flammability, and the presence of sulphur compounds. See also Section 16, "Other information".
- Handling temperature : This product can be handled at ambient temperatures.
- Hygiene measures : Avoid contact with skin. Do not breathe fume/ mist/ vapours. Do not ingest. Do not smoke. Do not eat and do not drink during use. Do not clean hands with dirty or oil-soaked rags. Do not re-use clothes, if they are still contaminated. Keep away from food and beverages.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store in dry, well ventilated area. Keep away from open flames, hot surfaces and sources of ignition. Do not smoke.
- Incompatible products : Keep away from: strong oxidants.
- Storage temperature : This product can be stored at ambient temperatures.
- Storage area : Storage area layout, tank design, equipment and operating procedures must comply with the relevant European, national or local legislation. Storage installations should be designed with adequate bunds so as to prevent ground and water pollution in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations.
- Packages and containers: : If the product is supplied in containers: Keep containers tightly closed and properly labelled. Keep only in the original container or in a suitable container for this kind of product.
- Packaging materials : For containers, or container linings use materials specifically approved for use with this product. Recommended materials for containers, or container linings use mild steel, stainless steel. Some synthetic materials may be unsuitable for containers or container linings depending on the material specification and intended use. Compatibility should be checked with the manufacturer.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

Distillates (petroleum), solvent-refined light paraffinic (64741-89-5)		
Austria	MAK (mg/m ³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Belgium	Limit value (mg/m ³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Denmark	Grænseværdi (langvarig) (mg/m ³)	1 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Denmark	Grænseværdi (kortvarig) (mg/m ³)	2 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Hungary	AK-érték	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
The Netherlands	MAC TGG 8h (mg/m ³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Spain	VLA-ED (mg/m ³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Spain	VLA-EC (mg/m ³)	10 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Sweden	Nivågränsvärde (NVG) (mg/m ³)	1 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)

Sweden	Kortidsvärde (KTV) (mg/m ³)	3 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
United Kingdom	WEL TWA (mg/m ³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
United Kingdom	WEL STEL (mg/m ³)	10 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Canada (Quebec)	VECD (mg/m ³)	10 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Canada (Quebec)	VEMP (mg/m ³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
USA - ACGIH	ACGIH TLV®-TWA (mg/m ³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
USA - ACGIH	ACGIH TLV®-STEL (mg/m ³)	10 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
USA - NIOSH	NIOSH REL (TWA) (mg/m ³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
USA - NIOSH	NIOSH REL (STEL) (mg/m ³)	10 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
USA - OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Distillates (petroleum) hydrotreated light paraffinic (64742-55-8)		
Austria	MAK (mg/m ³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Belgium	Limit value (mg/m ³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Denmark	Grænseværdi (langvarig) (mg/m ³)	1 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Denmark	Grænseværdi (kortvarig) (mg/m ³)	2 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Hungary	AK-érték	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
The Netherlands	MAC TGG 8h (mg/m ³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Spain	VLA-ED (mg/m ³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Spain	VLA-EC (mg/m ³)	10 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Sweden	Nivågränsvärde (NVG) (mg/m ³)	1 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Sweden	Kortidsvärde (KTV) (mg/m ³)	3 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
United Kingdom	WEL TWA (mg/m ³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
United Kingdom	WEL STEL (mg/m ³)	10 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Canada (Quebec)	VECD (mg/m ³)	10 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Canada (Quebec)	VEMP (mg/m ³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
USA - ACGIH	ACGIH TLV®-TWA (mg/m ³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
USA - ACGIH	ACGIH TLV®-STEL (mg/m ³)	10 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
USA - NIOSH	NIOSH REL (TWA) (mg/m ³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
USA - NIOSH	NIOSH REL (STEL) (mg/m ³)	10 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
USA - OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)

Phenol, isopropylated, phosphate (3:1) [Triphenyl phosphate >5%] (68937-41-7)		
Austria	MAK (mg/m ³)	3 mg/m ³ (Reference: CAS 115-86-6, Triphenylphosphate)
Austria	MAK Short time value (mg/m ³)	6 mg/m ³ (Reference: CAS 115-86-6, Triphenylphosphate)
Belgium	Limit value (mg/m ³)	3 mg/m ³ (Reference: CAS 115-86-6, Triphenylphosphate)
Denmark	Grænseværdi (langvarig) (mg/m ³)	3 mg/m ³ (Reference: CAS 115-86-6, Triphenylphosphate)
Denmark	Grænseværdi (kortvarig) (mg/m ³)	6 mg/m ³ (Reference: CAS 115-86-6, Triphenylphosphate)
Finland	HTP-arvo (8h) (mg/m ³)	3 mg/m ³ (Reference: CAS 115-86-6, Triphenylphosphate)
Finland	HTP-arvo (15 min) (mg/m ³)	6 mg/m ³ (Reference: CAS 115-86-6, Triphenylphosphate)
France	VME (mg/m ³)	3 mg/m ³ (Reference: CAS 115-86-6, Triphenylphosphate)
Ireland	OEL (8 hours ref) (mg/m ³)	3 mg/m ³ (Reference: CAS 115-86-6, Triphenylphosphate)
Spain	VLA-ED (mg/m ³)	3 mg/m ³ (Reference: CAS 115-86-6, Triphenylphosphate)
United Kingdom	WEL TWA (mg/m ³)	3 mg/m ³ (Reference: CAS 115-86-6, Triphenylphosphate)
USA - ACGIH	ACGIH TLV®-TWA (mg/m ³)	3 mg/m ³ (Reference: CAS 115-86-6, Triphenylphosphate)
USA - NIOSH	NIOSH REL (TWA) (mg/m ³)	3 mg/m ³ (Reference: CAS 115-86-6, Triphenylphosphate)
USA - OSHA	OSHA PEL (TWA) (mg/m ³)	3 mg/m ³ (Reference: CAS 115-86-6, Triphenylphosphate)

eni Rolling TNX

DNEL/DMEL (General population)

Long-term - local effects, inhalation = mg/m³/day**Distillates (petroleum), solvent-refined light paraffinic (64741-89-5)**

DNEL/DMEL (Workers)

Long-term - systemic effects, inhalation = 5,4 mg/m³/day (DNEL, Mineral base oil mist, severely refined, DMSO extract <3% m/m)

DNEL/DMEL (General population)

Long-term - local effects, inhalation = 1,2 mg/m³/day (DNEL, Mineral base oil mist, severely refined, DMSO extract <3% m/m)**Distillates (petroleum) hydrotreated light paraffinic (64742-55-8)**

DNEL/DMEL (Workers)

Long-term - systemic effects, inhalation = 5,4 mg/m³/day (DNEL, Mineral base oil mist, severely refined, DMSO extract <3% m/m)

DNEL/DMEL (General population)

Long-term - local effects, inhalation = 1,2 mg/m³/day (DNEL, Mineral base oil mist, severely refined, DMSO extract <3% m/m)**Phenol, isopropylated, phosphate (3:1) [Triphenyl phosphate >5%] (68937-41-7)**

DNEL/DMEL (Workers)

Acute - systemic effects, dermal 200 mg/kg bodyweight/day

Acute - systemic effects, inhalation 20,1 mg/m³

Acute - local effects, dermal 16

Long-term - systemic effects, dermal 4,17 mg/kg bodyweight/day

Long-term - systemic effects, inhalation 0,29 mg/m³

DNEL/DMEL (General population)

Acute - systemic effects, dermal 100 mg/kg bodyweight

Acute - systemic effects, inhalation 5 mg/m³

Acute - systemic effects, oral	50 mg/kg bodyweight
Acute - local effects, dermal	8 mg/cm ²
Long-term - systemic effects,oral	0,04 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	0,07 mg/m ³
Long-term - systemic effects, dermal	2,08 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	0,00029 mg/l
PNEC aqua (marine water)	0,000029 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	≥ 112 mg/kg dwt
PNEC sediment (marine water)	≥ 0,0168 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	100 mg/l

Monitoring methods : Monitoring procedures should be chosen according to the indications set by national authorities or labour contracts.,Refer to relevant legislation and in any case to the good practice of industrial hygiene.

Note : The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accord with specific guidance within the European REACH regulation. The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs may be recommended by an individual company, a governmental regulatory body or an expert organization, such as the Scientific Committee for Occupational Exposure Limits (SCOEL) or the American Conference of Governmental Industrial Hygienists (ACGIH). OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). While also considered to be protective of health, OELs are derived by a process different from that of REACH.

8.2. Exposure controls

Appropriate engineering controls : Before entering storage tanks and commencing any operation in a confined area, carry out an adequate clean-up, and check the atmosphere for oxygen content, flammability, and the presence of sulphur compounds. See also Section 16, "Other information".

Personal protective equipment (for industrial or professional use) : Face shield. Gloves. Protective clothing. Safety glasses. Safety shoes or boots. Dust/aerosol mask.



Hand protection	: When there is a risk of contact with the skin, use hydrocarbon-resistant, felt-lined gloves. Adequate materials: nitrile (NBR) or PVC with a protection index > 5 (permeation time > 240 mins). Use gloves respecting all the conditions and within the limits set by the manufacturer. Replace gloves immediately in case of cuts, holes or other signs of damages or degradation. If necessary, refer to the EN 374 standard. Personal hygiene is a key element for an effective hand care. Gloves must be worn only with clean hands. After wearing gloves, hands must be carefully washed and dried.
Eye protection	: When there is a risk of contact with the eyes, use safety goggles or other means of protection (face shield). If necessary, refer to national standards or to the EN 166 standard.
Skin and body protection	: Long-sleeved overalls. If necessary, refer to the EN 340 and related standards, for definition of characteristics and performance according to the risk rating of the area. Antistatic non-skid safety shoes or boots, chemical resistant, if necessary heat resistant and insulated.
Respiratory protection	: Independently from other possible actions (technical modifications, operating procedures, and other means to limit the exposure of workers), personal protection equipment can be used according to necessity. Open or well ventilated spaces: in presence of oil mists and if the product is handled without adequate containment means: use full or half-face masks with filter for mists/aerosols. In case there is a significant presence of vapours (e.g. through handling at high temperature), use full or half-face masks with filter for hydrocarbon vapours. (EN 136/140/145). Closed or confined areas (e.g. tank interiors): the use of protection measures for airways (masks or self-contained breathing apparatus), must be assessed according to the specific activity, as well as level and duration of predicted exposure. (EN 136/140/145)
Thermal hazard protection	: If contact with hot product is possible or anticipated, gloves should be heat-resistant and thermally insulated.
Environmental exposure controls	: Do not discharge the product into the environment. Storage areas/installations should be designed with adequate bunds so as to prevent ground and water pollution in case of leaks or spills. Onsite wastewater treatment required. Prevent discharge of undissolved substance to or recover from onsite wastewater. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.
Consumer exposure controls	: No special requirements necessary, if handled at room temperature.

8.3. Hygiene measures

General protective and hygienic measures	: Avoid contact with skin and eyes, Do not breathe vapours or mists., Do not clean hands with dirty or oil-soaked rags., Do not keep dirty rags in the overall pockets., Do not drink, eat or smoke with dirty hands., Wash hands with water and mild soap, do not use solvents or other irritant products which have a defatting effect on the skin., Do not re-use clothes, if they are still contaminated.
--	---

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid, bright & clear.
Molecular mass	: Not applicable for mixtures
Colour	: Pale yellow.
Odour	: Slight odour of petroleum.
Odour threshold	: There are no data available on the preparation/mixture itself.
pH	: Not applicable
Relative evaporation rate (butylacetate=1)	: Negligible.
Melting point	: Pour point ≤ 0 °C (ASTM D 97)
Freezing point	: Not applicable
Boiling point	: > 200 °C (ASTM D 1160)

Flash point	: ≥ 145 °C (ASTM D 93)
Critical temperature	: Not applicable for mixtures
Self ignition temperature	: > 300 °C (DIN 51794)
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Critical pressure	: Not applicable for mixtures
Relative vapour density at 20 °C	: > 1 (according to composition)
Relative density	: No data available
Density	: ≤ 890 kg/m ³ (15 °C) (ASTM D 4052)
Solubility	: Water: Immiscible and insoluble
Log Pow	: Not applicable for mixtures
Log Kow	: Not applicable for mixtures
Viscosity, kinematic	: 11 - 13 mm ² /s (40 °C) (ASTM D 445)
Viscosity, dynamic	: No data available
Explosive properties	: None (according to composition).
Oxidising properties	: None (according to composition).
Explosive limits	: LEL ≥ 45 g/m ³ (Aerosol)

9.2. Other information

VOC content : = 0 % (EU, CH)

The above data (9.1 - 9.2) are typical values and do not constitute a specification.

SECTION 10: Stability and reactivity

10.1. Reactivity

This mixture does not offer any further hazard for reactivity, except what is reported in the following paragraphs.

10.2. Chemical stability

Stable product, according to its intrinsic properties (in normal conditions of storage and handling).

10.3. Possibility of hazardous reactions

None (in normal conditions of storage and handling). Contact with strong oxidizers (peroxides, chromates, etc.) may cause a fire hazard. A mixture with nitrates or other strong oxidisers (e.g. chlorates, perchlorates, liquid oxygen) may create an explosive mass. Sensitivity to heat, friction or shock cannot be assessed in advance.

10.4. Conditions to avoid

Keep away from strong oxidizers. Keep away from open flames, hot surfaces and sources of ignition. Avoid the build-up of electrostatic charge.

10.5. Incompatible materials

Strong oxidants.

10.6. Hazardous decomposition products

In exceptional cases (i.e prolonged storage in tanks contaminated with water, and presence of anaerobic sulfate-reducing microbial colonies), the product may undergo a degradation and generate small amounts of sulfur compounds, including H₂S. See also Section 16, "Other information".

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified (Based on available data, the classification criteria are not met) (according to composition)

eni Rolling TNX	
LD50 oral rat	≥ 2000 mg/kg bodyweight (Calculated data). This evaluation is based on the real characteristics of the components and their combination, taking into account the information provided by the suppliers.

LD50 dermal rabbit	≥ 2000 mg/kg bodyweight (Calculated data). This evaluation is based on the real characteristics of the components and their combination, taking into account the information provided by the suppliers.
LC50 inhalation rat (mg/l)	≥ 5 mg/l/4h (Calculated data). This evaluation is based on the real characteristics of the components and their combination, taking into account the information provided by the suppliers.

Distillates (petroleum), solvent-refined light paraffinic (64741-89-5)

LD50 oral rat	> 5000 mg/kg (OECD 401)
LD50 dermal rat	> 5000 mg/kg (OECD 402)
LC50 inhalation rat (mg/l)	> 5 mg/l/4h (OECD 403)

Distillates (petroleum) hydrotreated light paraffinic (64742-55-8)

LD50 oral rat	> 5000 mg/kg (OECD 401)
LD50 dermal rat	> 5000 mg/kg (OECD 402)
LC50 inhalation rat (mg/l)	> 5 mg/l/4h (OECD 403)

Phenol, isopropylated, phosphate (3:1) [Triphenyl phosphate >5%] (68937-41-7)

LD50 oral rat	≥ 5000 mg/kg
LD50 dermal rabbit	≥ 2000 mg/kg bodyweight
LC50 inhalation rat (mg/l)	≥ 5 mg/l/4h

Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met) (according to composition) pH: Not applicable
Serious eye damage/irritation	: Not classified (Based on available data, the classification criteria are not met) (according to composition) pH: Not applicable
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met) (according to composition) This product does not contain any significant amounts of substances classified as sensitizers (in any case < 0.1 % wt)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met) (according to composition) This product does not contain any significant amounts of substances classified as mutagenic by the EU (in any case < 0.1 % wt)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met) (according to composition) This product does not contain any significant amounts of substances classified as Carcinogenic by the EU (in any case < 0.1 % wt) All the mineral base oils contained in this product have a value < 3 % wt of DMSO extract, according to IP 346/92 (Nota L - Annex VI Reg (CE) 1272/2008, # 1.1.3)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met) (according to composition) This product does not contain any significant amounts of substances classified as Toxic for Reproduction by the EU (in any case < 0.1 % wt)
Specific target organ toxicity (single exposure)	: Not classified (Based on available data, the classification criteria are not met) (according to composition)
Specific target organ toxicity (repeated exposure)	: Not classified (Based on available data, the classification criteria are not met) (according to composition)

Distillates (petroleum), solvent-refined light paraffinic (64741-89-5)

LOAEL (oral,rat,90 days)	= 125 mg/kg bodyweight/day (OECD TG 408)
--------------------------	--

Distillates (petroleum) hydrotreated light paraffinic (64742-55-8)

LOAEL (oral,rat,90 days)	= 125 mg/kg bodyweight/day (OECD TG 408)
--------------------------	--

Aspiration hazard	: May be fatal if swallowed and enters airways. For all low-viscosity petroleum products (less than 20,5 mm ² /s at 40 °C), there is the risk of aspiration into the lungs. This may occur directly after ingestion, or subsequently in case of vomiting (spontaneous or induced).
-------------------	--

eni Rolling TNX

Viscosity, kinematic	11 - 13 mm ² /s (40 °C) (ASTM D 445)
----------------------	---

Potential Adverse human health effects and symptoms	: Aspiration into lungs can cause a chemical pneumonia. Prolonged and repeated skin contact may cause reddening, irritation and dermatitis. Contact with eyes may cause temporary reddening and irritation.
Other information	: None of the components of this product are listed as carcinogen by NTP, IARC, OSHA, EU or others. This product does not contain any significant amounts of substances classified as mutagenic by the EU (in any case < 0.1 % wt). This product does not contain any significant amounts of substances classified as Toxic for Reproduction by the EU (in any case < 0.1 % wt). This product does not contain any significant amounts of substances classified as sensitizers (in any case < 0.1 % wt).

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: According to the components, and by comparison with other products of the same type and composition, it is expected that this product has a toxicity for aquatic organisms between 10 and 100 mg/l, and must be regarded as Dangerous to the environment. An uncontrolled release to the environment may produce a contamination of different environmental compartments (soil, underground, surface water bodies, aquifers). Handle according to general working hygiene practices to avoid pollution and release into the environment.
Ecology - air	: This product has a low vapour pressure. A significant exposure may happen only if the product is used at high temperature, or in case of sprays and mists.
Ecology - water	: This product is not soluble in water. It floats on water and forms a film on the surface. The damage to aquatic organisms is of mechanical kind (immobilization and entrapment)

eni Rolling TNX	
LC50 fish 1	10 - 100 mg/l (Calculated data). This evaluation is based on the real characteristics of the components and their combination, taking into account the information provided by the suppliers.
EC50 Daphnia 1	10 - 100 mg/l (Calculated data).
ErC50 (algae)	10 - 100 mg/l (Calculated data). This evaluation is based on the real characteristics of the components and their combination, taking into account the information provided by the suppliers.
Mineral base oil, severely refined (light) (64741-89-5)	
LC50 fish 1	> 100 mg/l (LL 50)
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)
Reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-trans-butyl-4-hydroxyphenyl)propionate (125643-61-0)	
LC50 fish 1	> 74 mg/l (OECD 203, 96h, Brachydanio rerio)
EC50 Daphnia 1	> 100 mg/l (OECD 202, 24h)
ErC50 (algae)	≥ 3 mg/l (OECD 201, 72 h, Scenedesmus subspicatus)
Alcohols, C12-14 (80206-82-2)	
LC50 fish 1	≥ 100 mg/l (ISO 7346/2)
ErC50 (algae)	0,1 - 1 mg/l (OECD 201)
Distillates (petroleum) hydrotreated light paraffinic (64742-55-8)	
LC50 fish 1	> 100 mg/l (LL 50)
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)
Phenol, isopropylated, phosphate (3:1) [Triphenyl phosphate >5%] (68937-41-7)	
LC50 fish 1	1,6 mg/l (96h)
EC50 Daphnia 1	2,44 mg/l (48 h)

12.2. Persistence and degradability

eni Rolling TNX	
Persistence and degradability	A fraction of the constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions. .
Mineral base oil, severely refined (light) (64741-89-5)	
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.

Alcohols, C12-14 (80206-82-2)	
BOD (% of ThOD)	≥ 60 % ThOD

Distillates (petroleum) hydrotreated light paraffinic (64742-55-8)	
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.

12.3. Bioaccumulative potential

eni Rolling TNX	
Log Pow	Not applicable for mixtures
Log Kow	Not applicable for mixtures

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

eni Rolling TNX	
This substance/mixture does not meet the PBT criteria of REACH, annex XIII.	
This substance/mixture does not meet the vPvB criteria of REACH, annex XIII.	
Results of PBT-vPvB assessment	The components in this formulation do not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)
Component	
Mineral base oil, severely refined (light) (64741-89-5)	This substance/mixture does not meet the PBT criteria of REACH, annex XIII. This substance/mixture does not meet the vPvB criteria of REACH, annex XIII. This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)
Distillates (petroleum) hydrotreated light paraffinic (64742-55-8)	This substance/mixture does not meet the PBT criteria of REACH, annex XIII. This substance/mixture does not meet the vPvB criteria of REACH, annex XIII. This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)

12.6. Other adverse effects

Other adverse effects	: None.
Additional information	: This product has no specific properties for inhibition of bacterial activity. In any case, wastewater containing this product should be treated in plants that are suited for the specific purpose.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Waste treatment methods	: Do not dispose of the product, either new or used, by discharging into sewers, tunnels, lakes or water courses. Deliver to a qualified official collector. Dispose of empty containers and wastes safely.
Sewage disposal recommendations	: Dispose of in a safe manner in accordance with local/national regulations. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.
Waste disposal recommendations	: European Waste Catalogue code(s) (Decision 2001/118/CE): 13 02 05* (mineral-based non-chlorinated engine, gear and lubricating oils). This EWC code is only a general indication, and takes into account the original composition of the product and its intended use. The user has the responsibility of choosing the right EWC code, considering the actual use of the product, alterations and contaminations.
Additional information	: Empty containers may contain combustible product residues. Do not cut, weld, drill, burn or incinerate empty containers or drums, unless they have been cleaned, and declared safe.
Ecology - waste materials	: The product as it is does not contain halogenated substances.
EURAL code (EWC)	: 13 02 05* - Mineral-based non-chlorinated engine, gear and lubricating oils

SECTION 14: Transport information

In accordance with ADR / RID / ADNR / IMDG / ICAO / IATA

14.1. UN number

Not regulated for transport

14.2. UN proper shipping name

Proper Shipping Name	: Not applicable
Proper Shipping Name (IMDG)	: Not applicable
Proper Shipping Name (IATA)	: Not applicable
Proper Shipping Name (ADN)	: Not applicable
Proper Shipping Name (RID)	: Not applicable

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR)	: Not applicable
----------------------------------	------------------

IMDG

Transport hazard class(es) (IMDG)	: Not applicable
-----------------------------------	------------------

IATA

Transport hazard class(es) (IATA)	: Not applicable
-----------------------------------	------------------

ADN

Transport hazard class(es) (ADN)	: Not applicable
----------------------------------	------------------

RID

Transport hazard class(es) (RID)	: Not applicable
----------------------------------	------------------

14.4. Packing group

Packing group (UN)	: Not applicable
Packing group (IMDG)	: Not applicable
Packing group (IATA)	: Not applicable
Packing group (ADN)	: Not applicable
Packing group (RID)	: Not applicable

14.5. Environmental hazards

Dangerous for the environment	: No
Marine pollutant	: No
Other information	: None.

14.6. Special precautions for user

Special transport precautions	: None.
-------------------------------	---------

- Overland transport

Transport regulations (ADR)	: Not subject
-----------------------------	---------------

- Transport by sea

Transport regulations (IMDG)	: This product is not classified as dangerous goods for transport, but if is transported in BULK FORM, it may fall under the scope of MARPOL ANNEX I (Group 3 - "unfinished distillates, hydraulic oils and lubricating oils")
------------------------------	--

Limited quantities (IMDG)	: Not applicable
MFAG-No	: --

- Air transport

Transport regulations (IATA)	: Not subject
------------------------------	---------------

- Inland waterway transport

Transport regulations (ADN)	: Not subject
-----------------------------	---------------

- Rail transport

Transport regulations (RID)	: Not subject
-----------------------------	---------------

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

IBC code	: None.
----------	---------

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no substances with Annex XVII restrictions

No ingredients are included in the REACH Candidate list (> 0,1 % m/m).

Contains no REACH Annex XIV substances.

Relevant EU Legislation : Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). (et sequens).
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (et sequens).
Directives 89/391/CEE, 89/654/CEE, 89/655/CEE, 89/656/CEE, 90/269/CEE, 90/270/CEE, 90/394/CEE, 90/679/CEE, 93/88/CEE, 95/63/CE, 97/42/CE, 98/24/CE, 99/38/CE, 99/92/CE, 2001/45/CE, 2003/10/CE, 2003/18/CE (Health and safety on the workplace)
Directive 98/24/EC (protection of the health and safety of workers from the risks related to chemical agents at work).
Directive 92/85/CE (measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding)
Directive 2012/18/CE (Control of major-accident hazards involving dangerous substances)
Directive 2004/42/CE (Limitation of emissions of Volatile Organic Compounds)

VOC content : = 0 % (EU, CH)

15.1.2. National regulations

National adoption of EU Directives concerning health and safety on the workplace.

National laws on classification and labeling of dangerous substances/preparations (Adoption of Directive 67/548/CE and subsequent Adaptations to Technical Progress - ATP, and Directive 1999/45/CE).

National adoption of EU Directives concerning control of major-accident hazards involving dangerous substances (2012/18/CE).

Relevant national laws on prevention of water pollution.

Relevant national laws on protection of the health of pregnant workers (National adoption of Dir. 92/85/EEC).

National adoption of Directives 75/439/CEE - 87/101/CEE concerning disposal of used oils.

France

Maladies professionnelles (F) : RG 36 - Affections provoquées par les huiles et graisses d'origine minérale ou de synthèse

Germany

VwVwS Annex reference : Water hazard class (WGK) (D) 2, hazard to waters (Classification according to VwVwS, Annex 4)

WGK remark : Classification based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS)

VbF class (D) : Not applicable.

Storage class (LGK) (D) : LGK 10 - Combustible liquids

Employment restrictions : Employment prohibitions on the protection of young people at work according to § 22 section 1(6) JArbSchG have to be observed.

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Other information, restrictions and prohibition regulations : TRGS 900: Occupational Exposure Limits
 TRGS 800: Fire protection measures
 TRGS 555: Working instruction and information for workers
 TRGS 402: Identification and Assessment of the Risks from Activities involving Hazardous Substances: Inhalation Exposure
 TRGS 401: Risks resulting from skin contact - identification, assessment, measures
 TRGS 400: Risk Assessment for Activities involving Hazardous Substances

The Netherlands

Saneringsinspanningen : C - Lozing minimaliseren

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed

Recommendations Danish Regulation : Young people under 18 years are not allowed to use the product
 Pregnant/breastfeeding women working with the product must not be in direct contact with it

15.2. Chemical safety assessment**A chemical safety assessment has been carried out for the following components of this mixture:**

Distillates (petroleum), solvent-refined light paraffinic
 Reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-trans-butyl-4-hydroxyphenyl)propionate
 Distillates (petroleum) hydrotreated light paraffinic

SECTION 16: Other information

Indication of changes:

Modification according to Regulation (EC)1907/2006 and (EC) 830/2015. Formula. Classification of the substance or mixture. Adverse physicochemical, human health and environmental effects. Hazard statements (CLP). Precautionary statements (CLP). Ecology - general. EC50 Daphnia 1. ErC50 (algae). LC50 fishes 1. Water hazard class (WGK).

Abbreviations and acronyms:

	Complete text of the H phrases quoted in this Safety Data Sheet. These phrases are reported here for information only, and MAY NOT correspond to the classification of the product.
	<p>N/A = Not applicable. N/D = Not available ACGIH = American Conference of Governmental Industrial Hygienists API = American Petroleum Institute ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor CSR = Chemical Safety Report DNEL = Derived No Effect Level DMEL = Derived Minimum Effect Level EC50 = Effective Concentration, 50% EL50 = Effective Loading, 50 % EPA = Environmental Protection Agency IC50 = Inhibition Concentration, 50% LC50 = Lethal Concentration, 50% LD50 = Lethal Dose, 50% LL50 = Lethal Loading, 50% LOAEL = Low Observed Adverse Effects Level NOEL = No Observed Effects Level NOAEL = No Observed Adverse Effects Level OECD = Organization for Economic Cooperation and Development PNEC = Predicted No-Effect Concentration PBT = Persistent, Bioaccumulative, Toxic STOT = Single Target Organ Toxicity (STOT) RE = (Single Target Organ Toxicity) Repeated exposure (STOT) SE = (Single Target Organ Toxicity) Single exposure TLV@TWA = Threshold Limit Value@ - Time-Weighted Average TLV@STEL = Threshold Limit Value@ - Short Term Exposure Limit UVCB = Substance of Unknown or Variable composition, Complex reaction products or Biological materials vPvB = very Persistent, very Bioaccumulative WAF = Water Accommodated Fraction</p>

Data sources : This Safety Data Sheet is based on the real characteristics of the components and their combination, taking into account the information provided by the suppliers.

Training advice	: Provide adequate training to professional operators for the use of PPEs, according to the information contained in this Safety Data Sheet.
Other information	: Do not use the product for any purposes that have not been advised by the manufacturer. In exceptional cases (i.e prolonged storage in tanks contaminated with water, and presence of anaerobic sulfate-reducing microbial colonies), the product may undergo a degradation and generate small amounts of sulfur compounds, including H ₂ S. This situation is especially relevant in all those circumstances which require to enter a confined space, with direct exposure to the vapours. If this possibility is suspected, a specific assessment of inhalation risks from the presence of H ₂ S in confined spaces must be made, to help determine prevention measures and controls (i.e. PPE) appropriate to local circumstances, and adequate emergency procedures. If there is any suspicion of inhalation of H ₂ S (hydrogen sulphide), Rescuers must wear breathing apparatus, belt and safety rope, and follow rescue procedures. Send patient to hospital. Immediately begin artificial respiration if breathing has ceased. Administer oxygen if necessary.

Full text of H- and EUH-phrases:

Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Repr. 2	Reproductive toxicity, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
H304	May be fatal if swallowed and enters airways
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects
H413	May cause long lasting harmful effects to aquatic life

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Asp. Tox. 1	H304	Calculation method
Aquatic Chronic 3	H412	Calculation method

SDS EU (REACH Annex II) eni 2015

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product