



eni Codium LS 22

eni Codium LS 22 is a clear semi-synthetic oil with innovative features, created for the lubrication of textile machinery.

eni Codium LS 22 contains a synthetic component which, blended with carefully selected base oils refined to an extreme degree, allows this product to operate in working conditions far more severe than traditional textile oils can withstand. A well balanced additive treatment gives this lubricant the anti-wear properties now demanded by the most sophisticated applications.

CHARACTERISTICS (TYPICAL FIGURES)

eni Codium LS 22

Viscosity at 40°C	mm ² /s	20.9
Viscosity at 100°C	mm ² /s	4.19
Viscosity Index	-	102
Colour Saybolt	-	+23
Flash Point COC	°C	210
Pour Point	°C	-15
Mass Density at 15°C	kg/l	0.862

PROPERTIES AND PERFORMANCE

eni Codium LS 22 is a top-quality oil with the following features:

- excellent anti-wear and anti-rust properties for protection of lubricated components;
- excellent adhesive and anti-drip properties;
- good washability, indispensable for removal of traces of oil from the fabric;
- colourless, to minimize any effects of residual contamination after washing.

APPLICATIONS

eni Codium LS 22 is a special product developed for textile industry, in particular for the lubrication of knitwear machinery and stocking machine needles.

eni Codium LS 22 is also recommended for the lubrication of spindles of machine tools and of the pneumatic tools (lubrication in line).

SPECIFICATIONS

eni Codium LS 22 meets the requirements of the following specifications:

- ISO-L-AN
- ISO-L-FC