

# Eni i-Sint tech F 5W-30



## APPLICATIONS

**Eni i-Sint tech F 5W-30** is a synthetic technology lubricant developed for Ford cars of the latest generation, requiring an oil that meets the WSS-M2C913-D specification. The product is suitable for those passenger cars for which the manufacturer prescribes lubricants conforming to the 912 or 913 A / B / C specifications.

## CUSTOMER ADVANTAGES

- The viscosimetric properties of **Eni i-Sint tech F 5W-30** guarantee excellent cold start even at very low temperatures always guaranteeing the best lubrication to engine components.
- The product reduces friction, actively contributing to fuel economy with a simultaneous reduction of carbon dioxide (CO<sub>2</sub>) emissions.
- **Eni i-Sint tech F 5W-30** effectively prevents wear, ensuring maximum mechanical protection even under particularly hard operating conditions.
- The presence of components with low volatility and high thermal stability helps to limit the effects of oil consumption.

## SPECIFICATIONS AND APPROVALS

- ACEA A1/B1
- ACEA A5/B5
- API SL/CF
- Ford WSS-M2C913-D
- Renault RN 0700



# Eni i-Sint tech F 5W-30



## CHARACTERISTICS

Properties	Method	UNIT	Typical
Density at 15°C	ASTM D 4052	kg/m <sup>3</sup>	853
Viscosity at 100°C	ASTM D 445	mm <sup>2</sup> /s	10.1
Viscosity at 40°C	ASTM D 445	mm <sup>2</sup> /s	56
Viscosity Index	ASTM D 2270	-	171
Viscosity at -30°C	ASTM D 5293	mPa·s	6400
Flash point (COC)	ASTM D 92	°C	217
Pour point	ASTM D 97	°C	-39

