

AGIP HYDRAULIC OIL TNX

AGIP HYDRAULIC OIL TNX 46 is a hydraulic fluids specially developed to be used in the hydraulic plants of Sendzimir rolling plants, because its formula is studied to be highly compatible with rolling fluids.

CHARACTERISTICS (TYPICAL FIGURES)

HYDRAULIC OIL TNX 46

Viscosity at 40°C	mm²/s	43
Viscosity at 100°C	mm²/s	7.4
Viscosity Index	-	136
Flash point C.O.C	°C	188
Mass density at 15°C	kg/l	0.864

PROPERTIES AND PERFORMANC

- AGIP HYDRAULIC OIL TNX 46 is a hydraulic fluid with the following good properties: antioxidant, antiwear, antirust, antifoam and demulsibility to be particularly suitable for hydraulic system of metals rolling.
- AGIP HYDRAULIC OIL TNX 46 is a product formulated with selected base oils and additives, that in
 case of hydraulic fluid losses, they don't stain the rolled metal, because its additive system is highly
 compatible with that of the rolling fluid.

APPLICATIONS

AGIP HYDRAULIC OIL TNX 46 is formulated with special base oils and selected additives, that in case of accidental leakages of hydraulic oil in the rolling fluid, this will be not staining the sheet or foils of the following metals: titanium, stainless steel, copper and aluminium.